

# PT15-45 Series D.O.T. Push-in Fittings



800.909.4988  
info@rankinusa.com

**RANKIN**   
COMPONENTS THAT AUTOMATE

<b>Material:</b>	Brass	
<b>Working Temperature:</b>	-50 ÷ 100	C°
<b>Working Temperature:</b>	-58 ÷ 212	F°
<b>Working Pressure (max):</b>	20	bar
<b>Working Pressure (max):</b>	290	psi
<b>Vacuum:</b>	-99	kPa
<b>Vacuum:</b>	29"	Hg
<b>Conformity:</b>	RoHS	

**Conformity:**  
**Conformity:**  
**Conformity:**  
**Conformity:**  
**Application**

Pneumatic circuits for truck and Trailers : Air Suspension, Braking Systems, Transmissions, locking doors and windows, Seat adjustment, Instrumentation, Air conditioning systems, horn, wiper motors, valves, cylinders and accessories

## PT15-45

Taper Swivelling Elbow Fittings, male 45°



## PT15-45

## 3D

CODE	TYPE	TUBEOD	TUBEID	IDIN	D1NPTF	D2	D2IN	L1	L1IN	L2	L2IN	L3	L3IN	HEX	G	OZ	WTF	WPP	TVH
2T050031-45	PT15 1/4 1/8 45°	1/4	4.2	.165	1/8	12	.472	8.5	.335	23	.906	22.5	.886	1/2	-	-	-58 ÷ 212	290	29"
2T050032-45	PT15 1/4 1/4 45°	1/4	4.2	.165	1/4	12	.472	13	.512	28	1.102	22.5	.886	9/16	-	-	-58 ÷ 212	290	29"
2T050052-45	PT15 3/8 1/4 45°	3/8	6.2	.244	1/4	16	.630	13	.512	29	1.142	26	1.024	11/16	-	-	-58 ÷ 212	290	29"
2T050053-45	PT15 3/8 3/8 45°	3/8	6.2	.244	3/8	16	.630	13	.512	29.5	1.161	26	1.024	11/16	-	-	-58 ÷ 212	290	29"
2T050054-45	PT15 3/8 1/2 45°	3/8	6.2	.244	1/2	16	.630	17	.669	35	1.378	26	1.024	7/8	-	-	-58 ÷ 212	290	29"

2T050063-45	PT15 1/2 3/8 45°	1/2	9.2	.362	3/8	20	.787	13	.512	32	1.260	28.7	1.130	13/16	-	-	-58 ÷ 212	290	29"
2T050064-45	PT15 1/2 1/2 45°	1/2	9.2	.362	1/2	20	.787	17	.669	36.5	1.437	28.7	1.130	7/8	-	-	-58 ÷ 212	290	29"